

CHROMA-CHEM® AK 942D

**Solvent-Based Colorants
for Industrial Point-of-Sale &
In-Plant Applications**

chroma-chem 

- **Best-in-class quality for color retention, dispensability, and consistency in a wide variety of chemistries**
- **Specially designed for use in high-performance, non-aqueous, industrial and maintenance coating**
- **Colorant formulations minimize dispersing resin and additive levels**
- **Colorants pigments provide wide range of shades**
- **Excellent control on tinting strength volume**
- **Good compatibility with large number of maintenance and industrial coating**
- **Available for volumetric dispensing and in-plant tinting**

CHROMA-CHEM® 942D

Industrial Colorants for Solvent-Based Applications

General Description

Using our global technological leadership to meet evolving customer requirements, Chromaflo Technologies introduces the CHROMA-CHEM® AK942D range of industrial colorants. This latest development further expands Chromaflo's wide range of industrial colorants and color systems.

CHROMA-CHEM® AK 942D Colorants, which are based on an aldehyde ketone resin, have been specifically designed for both in-plant and machine tinting of industrial solvent-based coatings. The choice of resin together with the unique combination of resin, solvent, pigment and surfactants used in the CHROMA-CHEM® AK942D products result in a range, offering very broad compatibility, in a wide range of commonly used industrial coatings systems such as:

- Polyurethanes
- Epoxies
- Acrylics
- Polyesters
- Alkyds
- Cellulosic lacquers
- Chlorinated rubber
- Stoving enamels
- Other solvent-based systems

Designed to meet the exacting needs of modern industrial paint procedures, CHROMA-CHEM® AK942D Colorants provide the following advantages that bring additional value to your current color system:

1. Broad compatibility means that sacrifices in paint properties do not need to be made to achieve compatibility.
2. The pigments were selected and the colorants designed to achieve an optimum balance between performance and economics for the paint formulator.
3. The colorants were developed to facilitate color matching of widely used industrial color standards such as RAL, AS2700 and BS.
4. Volumetrically and gravimetrically dispensable colorants can be used both as in-plant and point-of-sale industrial color systems.
5. Amine-free colorants do not react with isocyanates, as the resin system contains no water or free amines.

CHROMA-CHEM® AK942D Colorants satisfy the needs of the industrial market today in terms of compatibility, pigment choice, gloss, pot life, weather resistance, hardness, dry time and other key performance factors.

Tint Strength Control

CHROMA-CHEM® AK 942D Colorants are controlled to a tinting strength tolerance of $\pm 2\%$ by volume, $\Delta E < 0.5$ vs. standard. This close control allows for accurate reproduction of color in our Industrial Color System, in custom systems, or for in-plant use.

Rheological properties of the colorants are also controlled to allow for use in volumetric tinting machines.




Volumetric formulas using CHROMA-CHEM® AKD942D Colorants for common color collections such as Portfolio of Color, Federal Standard 595b, RAL colors and British Standard colors can be developed to suit a variety of paint systems.

Please contact your Chromaflo Technologies Technical Service Laboratory for further information.

chroma-chem 



CHROMA-CHEM® 942D - Typical Physical Properties

Masstone	Tint	Product Code	Colorant Description	CI Pigment	Specific Gravity	% Composition by Weight			VOC* g/L
						Pigment Solids	Vehicle Solids	Volatiles	
		9429960	HS Black D21	Black 7	1.19	18.7	41.1	30.3	359
		9421863	Yellow Oxide D22	Yellow 42	1.75	57.1	23.0	19.9	347
		9427262	Blue D23	Blue 15:4	1.07	17.5	46.4	36.1	386
		9425502	Green D24	Green 7	1.10	18.9	42.8	38.3	420
		9420061	White D25	White 6	2.07	69.0	14.7	16.1	333
		9420925	Orange D26	Orange 36	1.10	23.7	43.8	32.5	355
		9422802	Golden Yellow D28	Brown 24	2.07	67.6	17.6	14.7	304
		9429451	Bordeaux D29	Violet 19	1.06	16.9	46.0	35.6	379
		9427265	Blue D30	Blue 15:6	1.07	25.0	29.8	45.2	485
		9421063	Red Oxide D31	Red 101	2.00	62.9	20.7	16.4	327
		9422803	Yellow D32	Yellow 138	1.19	31.7	34.1	32.3	383
		9422502	Medium Yellow D33	Yellow 83	1.05	18.0	46.1	36.0	377
		9429955	Black D34	Black 7	1.50	3.5	29.3	22.9	343
		9420715	Red D35	Red 254	1.14	35.1	34.0	31.0	352
		9422804	HS Yellow D81	Yellow 138	1.27	44.8	23.6	31.6	400

All data obtained directly from pigment suppliers, individual testing is recommended. Lightfastness is measured against the blue wool standard on a scale of 1 to 8 where 1 = severe change and 8 = no change.

Locations

America

Chromaflo Technologies Corp

2600 Michigan Avenue
P.O. Box 816
Ashtabula, Ohio
44005 USA
PHONE: +1 440 997-5137
www.chromaflo.com

Europe

Chromaflo Technologies B.V.

Ankerkade 101
6222 NL Maastricht
Netherlands
PHONE: +31 43 352-7700

Asia-Pacific

Chromaflo Technologies Australia Pty Ltd

30-32 Commercial Drive
P.O. Box 996 Dandenong
3175 Victoria Australia
PHONE: +61 3 9703-8888

Malaysia

Chromaflo Technologies (M) Sdn Bhd

1Lot 622 Lebuhraya Raja Lumu,
Pandamaran Industrial Estate,
42000 Port Klang,
Selangor Darul Ehsan, Malaysia,
PHONE: +603 3163 1018
FAX: +603 3163 1019

China

Chromaflo Technologies China Ltd.

No.655. Shenfu Road,
XinZhuang Industrial Zone,
Shanghai, 201108
P.R.China
PHONE: +86 21 2416 9200

Thailand

Thailand Representative Office

Regus Sathorn Square
No. 3769, 37th Floor,
98 North Sathorn Road
Silom, Bangkok,
Bangkok 10500
Thailand
PHONE: +668 7088 0500

India

Chromaflo Technologies India Pty Ltd

J-15 Taloja MIDC,
Taloja,
Raigad District, Maharashtra State
India 410208
PHONE: +91 22 2778 8521

South Africa

Chromaflo Technologies Africa

17 Crusher Road
Crown Ext. 3
Johannesburg 2095
South Africa
PHONE: +27 11 084 1600



Health & Safety
OHSAS 18001
SAI GLOBAL



Quality
ISO 9001
SAI GLOBAL



Environment
ISO 14001
SAI GLOBAL

This information and all further technical advice is based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.